

AQUATERR

Valve Actuating Receiver Wall Mount Version

The only wireless valve actuator available with five mile uninterrupted reception

Lowest Cost to Automate. The cost of the automation equipment is far less expensive than the cost to dig and bury wires, especially for long or obstacle-ridden runs. It is more cost effective to replace buried wire system with the Aquaterr wireless VAR system than to continuously repair wires that have been chewed by rodents or damage by earth moving equipment.

Non line-of-site radio signals. Line-of-site transmitters have to be able to “see” their receivers. Obstacles such as building, trees, and hill block transmissions. With Aquaterr’s wireless system, these obstacles are transparent. The non-line-of-site signals are reliably received by Aquaterr VARs for a radius of five miles.

Qualifies as a water conservation green product. Check with your local governing agencies to see if a green product rebate may apply to you. When moisture sensors are used, watering is only permitted when soil moisture properties require watering, as individually programmed for your watering needs. Sensors buried at various depths determine if watering should begin. Safety overrides are individually programmed for each valve to prevent over watering.

Uses an AC plug in power supply.

No radio license purchase is required for this radio system, and no radio fees. These radio communication airwaves are FREE!



VAR-1
VAR-2
VAR-4

How it works.

Interfaces seamlessly between your existing Commercial Irrigation Controller and you valve’s latching solenoid. Receives encoded and redundant radio signals from an Aquaterr radio transmitter, which communicates commands originating from your irrigation controller.

- 5-mile reception regardless of terrain.
- True non-line-of-site wireless communications.
- Works with any controller, any valve; any solenoid.
- No radio licensing fees. No cellular costs.
- Encoded redundant transmission assure communication regardless of weather or electrical interference.
- Significant cost saving for installation and maintenance.
- Eligible for government rebates.
- Uses an AC plug in power supply.

AQUATERR

Valve Actuating Receiver Wall Mount Version

Aquaterr's Pole Mount Valve Actuating Receiver's (VAR's) are ideal for both agriculture and turf applications. Whether your system is manual or wired, if you are ready to implement an automated irrigation plan, Aquaterr's family of wireless solutions may be your best option.

For manual system, wireless conversion is the least cost route towards automations. Simply change to an electric valve with latching solenoid. No digging to bury wires. It operates with any manufacturer's commercial irrigation controller, designed to control solenoids.

System with buried wires often experience problems from earth moving equipment, or ground creatures chewing wires. Sometimes it is just not economical to bury more wire, especially in turf applications where concrete or other obstacles are in the wire path.

The best automation choice, the one that offers the fastest return on investment in most cases, is wireless. In addition, Aquaterr's wireless solution has the security to assure your valves always turn on and off at your command. Aquaterr's wireless system has no radio licensing fees, unlike most others. Most importantly, the radio signals are fool-proof, and unable to be tempered with. Each transmitted instruction is encoded, with redundancy and overwatering, protection to assure successful irrigation.



The Aquaterr Programmer portable device is used to program various unique parameters in both the VAT (transmitter) and VAR (receiver). See User Manual for full details.

Specifications

	VAR-2/VB Operate 2 Valves	VAR-4/VB Operate 4 Valves
Signal Receiving Range	5 miles	5 miles
Operating Voltage	5V DC	5V DC
Battery Type	5V DC Power Supply	5V DC Power Supply
Output Operation	9-12 v latching solenoid	9-12 v latching solenoid
Max Wire Run (cum)	Up to 1000 ft	Up to 1000 ft
Wire Type	14 - 16 AWG insulated	14 - 16 AWG insulated
Fail Safe Shutdown	Programmable	Programmable
Manual Actuate	Switch/Programmer	Switch/Programmer
Unit Identification	Field programmable	Field programmable
Enclosure	Weatherproof UV resistant plastic	Weatherproof UV resistant plastic
Mounting Height	2 to 6 feet (61 to 183 cm)	2 to 6 feet (61 to 183 cm)
Mounting Method	Wall or flat surface	Wall or flat surface
Size	5.5 L x 7 W x 4.5 H Inches (13.97 x 17.78 x 11.43 cm)	5.5 L x 7 W x 4.5 H inches (13.97 x 17.78 x 11.43 cm)
Weight	1.35 lbs (0.613 kg)	1.60 lbs (0.613 kg)
Shipping Size	7.5 x 9 x 6.5 inches, 19.05 x 22.86 x 16.51 cm	7.5 x 9 x 6.5 inches, 19.05 x 22.86 x 16.51 cm
Shipping Weight *	2.35 lbs (1.06 kg)	2.60 lbs (1.18 kg)
Warranty	One year	One year

Aquaterr

1685 Babcock Street, Suite A, Costa Mesa, CA 92627, USA

Telephone: 949.646.7274 Fax: 949.646.7493

Email: office@aquaterr.net

www.aquaterr.net